

# Safety and Assembly Instructions

## IMPORTANT

READ AND FOLLOW ALL SAFETY INFORMATION AND INSTRUCTIONS, KEEP FOR FUTURE REFERENCE



**WARNING!**  
CHOKING HAZARD-SMALL PARTS, NOT FOR CHILDREN UNDER 3 YEARS.  
MAXIMUM WEIGHT SHOULD NOT EXCEED 100KG.  
DO NOT USE WITHOUT ADULT SUPERVISION.  
ADULT ASSEMBLY REQUIRED.

## ESSENTIAL INFORMATION

- Recommended for children 3+ years
- Do not leave child unattended while in use
- CAUTION: Use only under adult supervision
- Good safety practices should be followed at all times
- Read all instruction before using this product.


1-2 adults needed for assembly. Maximum weight capacity: 100KGS.

Hanging hardware not included. Ideally, the swing body should be hung over grass, sand, wood chips, or other soft surfaces. It should not be hung over concrete, asphalt, or other hard surfaces. Distance from ground should not exceed 40cm; there are two S-hooks attached to the ropes to allow for adjustment of the rope length.

Please be sure to examine the ropes regularly to check for wear. Rope will, in time, degrade. If the color of the rope has become pale, frays easily, or gives off a powdery material when rubbed between the fingers, we recommend you replace the rope.


Equipment should be hung in such a way that a distance of at least 2m is clear on either side. Can be hung on an A-frame or swing set or on a tree limb of a diameter of at least 25cm.

Tools Required(not included in the packaging)



## Assembling your swing

This swing is designed to be tight, so it does take some effort to put together.

 <p>1. Swing arrives in 4 pieces plus 2 hanging ropes and a seat mat for assembly.</p>	 <p>2. Put the frame tubes and seat mat on floor. Check which end of the tubes fit together.</p>	 <p>3. Put the 4 frame tubes evenly into the sleeves one by one.</p>
 <p>4. Put one small socket into big socket and repeat on the opposite side. Connect a swing bolt to each of these two opposite joins.</p>	 <p>5. Then fold in half and simultaneously join the two halves together. This may require help from a second person. At this point you must make sure the loops are evenly spaced and <u>not</u> pulling at an angle. Keep your fingers clear of the join.</p>	 <p>6. Then you have a round platform.</p>
 <p>7. Finally attach the remaining two swing bolts.</p>	 <p>8. Lock it with screw nut, do not forget the washer.</p>	 <p>9. Assembly is finished and ready to swing.</p>

## Ensuring Safety of the Swing

Clearance distance should be 2m around the swing.

A fall onto a hard surface can result in serious injury to the equipment user.

Do not use the equipment until properly installed.

This swing is not to be used in any other manner other than its intended use.

Adult supervision is required.

Adults should verify that the hanging ropes are secured and cannot be looped back on the

swing.

It is important for adults to instruct children to:

- Dress appropriately while using the swing (avoid ponchos, scarves, and other loose-fitting clothing that is potentially hazardous)
- Sit in the center of the swing with full weight on the seat if swinging alone
- Avoid swinging empty seats

It is important for adults to instruct children **NOT to**

- Walk close to, in front of, behind, or between moving items
- Twist ropes or loop them over the top support bar since such action may reduce the strength of the rope
- Get off the swing while it is in motion
- Climb on the swing when it is wet.
- Attach additional items to the swing.

## **Maintaining the Swing**

At the beginning of the each play season, adults should:

- Check and tighten hardware if necessary.
- Check all protective coverings on pipes, edges, and corners, Replace if they are loose, cracked, or missing.
- Check all moving parts including swing seat, ropes for wear, rust, or other deterioration, Replace as needed. The hardware used for this swing (binding post, screw, S hook, lock washer, flat washer, and metal ring) can be found at local hardware store.
- Check metal parts for rust, if found, and repaint using a non-lead-based paint meeting the EN71 requirements.
- If the swing is hung from swing set frame, then lubricate all metallic moving parts that are attached by a metal connection.
- If the swing is hung from a tree branch, then rake and check depth of loose-fill protective surfacing materials (such as mulch or sand) to prevent compaction and to maintain appropriate depth (Min amount is 25cm), replace as needed.

At the end of each play season, or when the weather is bad, adults should:

- Remove the swing from its outdoor location.
- Store the swing in a dry environment.

## **Disposing of the swing**

To dispose of the swing, first disassemble it, Dispose of it in such a way that no unreasonable hazards will exist at the time that the swing is discarded.